

JaCa tools ApS

Tlf: 36 91 52 20 • salg@jacatools.dk



* HM ubelagt
** HM Cutinox

D ₁	L ₁	D ₂	D _{h5}	L	DKR *	DKR **
0.10	0.2	0.01	3	38	396	426
0.20	0.4	0.02	3	38	324	356
0.30	0.6	0.03	3	38	264	300
0.40	0.8	0.04	3	38	228	264
0.50	1.0	0.05	3	38	168	198
0.60	1.2	0.06	3	38	168	198
0.70	1.4	0.07	3	38	168	198
0.80	1.6	0.08	3	38	168	198
0.90	1.8	0.09	3	38	168	198
1.0	2.0	0.10	3	38	168	198
1.10	2.2	0.11	3	38	168	198
1.20	2.4	0.12	3	38	168	198
1.30	2.6	0.13	3	38	168	198
1.40	2.8	0.14	3	38	168	198
1.50	3.0	0.15	3	38	168	198
2.0	4.0	0.20	3	38	168	198
2.50	5.0	0.25	3	38	168	198
3.0	6.0	0.30	4	50	228	270
4.0	8.0	0.40	5	50	276	312
5.0	10.0	0.50	6	50	318	360
6.0	12.0	0.60	8	60	342	390
8.0	16.0	0.80	10	70	456	516
10.0	18.0	1.00	12	70	564	654
12.0	20.0	1.20	12	70	624	708



Acier + Pb	Acier faibl. allié	Acier fort. allié	Acier inox aust.	Fontes
Super alliages Ni / Co	Titane, alliage de titane	Alliage Cu Argent Or	Alliage Cu difficile	Alu

